

INSTRUCTION SHEET


QUICKTIMER - LAP TIMER




INSTALLATION / WIRING

- **Mounting The Gauge:** Drill a 2-1/16" hole for gauge installation. Place the gauge, slide the bracket over the two mounting studs, and secure with the provided nylon lock nuts.

- **Wiring Connections:**

 **RED WIRE:** goes to a switched positive (+) power source

 **BLACK WIRE:** goes to a good clean ground/negative (-) source.

- **Antenna Setup:** Plug the antenna into the 4-pin connector on the back of the gauge. Use adhesive backing to secure the antenna.

Tip: Route the antenna wire away from other wiring to reduce interference.



CALIBRATION/SET-UP

- **Clearing Gauge Memory / Erasing Recall:** Press and hold the button on the gauge face for 10 seconds. The gauge will flash red and display "CLR," clearing the memory.
- **Acquiring Signal:** Power on the gauge outdoors for better signal acquisition. If there is no signal, the gauge flashes red and displays "---." Once a signal is acquired, it flashes green and displays "OK," and the antenna flashes red.


ON TRACK FUNCTIONING

- **Setting Your Start/Finish Point:** When the gauge displays "SET," drive to your set point on the track, then press the button to record. Tip: Set your point while driving as slow as possible.
- **Start Timing:** After setting the track point, the gauge displays "OK," then "GO." When a lap is completed, the gauge shows your lap time with two white lights at the top.
- **Lap Time Comparisons:** After the second lap, the gauge shows the previous lap time. On subsequent laps, the gauge displays a time differential with a green or red light: Green if the lap was faster and Red if slower than the previous lap. (Example: If the lap is 1.1 seconds faster, the gauge flashes green and displays "1.1.")

POST-SESSION FUNCTIONS

- **Recall Fastest Lap:** Press the button once to display the fastest lap recorded.
- **Erase Fastest Lap Recall:** Press and hold the button for 3 seconds while in recall mode to erase the fastest lap in the previous session. The gauge flashes green and displays "OK" to confirm recall has been erased.
- **Clear Track Point for New Set-Up:** While not in recall mode, press and hold the button for 10 seconds to clear the set point and prepare for a new track point.

REV.10-24

 **WARNING:** This product can expose you chemicals including lead, which is/are known to the state of California to cause cancer, birth defects or other reproductive harm. For more information, go to: www.P65Warnings.ca.gov



www.quickcar.com
1-800-997-7333

170 Business Park Dr,
Lebanon, TN 37090